



All the patents are held accountable counterfeiting.

Features



Green Power

- Standard/Din Rail Mounting Dual Purpose
- Easy mounting (one-step installation)
- Full Range Input with PFC
- Comply with High Efficiency Power 80Plus Criterion
- 91% High Efficiency
- Build-in output stability monitor
- Split rail & Series connection possible
- Convection cooled high reliability
- 100% burn-in test
- EN 62368 approved
- 2 years warranty
- Output modify range: 5V~60VDC

DIMENSIONS:100(H)*83(D)*49(W)mm

WEIGHTS: 365g

General specifications

INPUT

Input range 90~264VAC
120~380VDC

Input frequency 47~63Hz

Inrush current (25°C) 20A/110VAC
40A/220VAC

Power factor 95% Min.

OUTPUT

Hold-up time 13ms

Short protection Autorecovery

Over load protection Automatic power limited

1A power ready relay contacts are built in VAT module.

Detail specifications

120 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) ¹			Ripple & Noise ⁴	Line REG. ²	Load REG. ³	Efficiency ⁵	O.V.P
		Min.	Rated	Max.					
RPH1120D-12CED	V : +12V ±10%	0A	10.0A	10.0A	120mV	±1%	±1%	91% Ref.	17.1 ~ 18.9V
RPH1120D-24CED	V : +24V ±10%	0A	5.0A	5.0A	240mV	±1%	±1%	89% Ref.	31.4 ~ 34.7V
RPH1120D-48CED	V : +48V ±10%	0A	2.5A	2.5A	480mV	±1%	±1%	91% Ref.	64.6 ~ 71.4V

Please Choose Fit Function, And Fill In The Blank With Suitable Words.

Order Model: RPH1120D-24C

Optional Function:

Terminal Block: "T" : PCB Barrier Terminal Block with Voltage Monitor

"E" : Mini Terminal Block with Voltage, Current, Temperature Monitor

Option: " " : Power Ready Relay Function

"N" : No Power Ready Relay Function

Intelligent Monitor Alarm Instructions:

- Voltage alarms when output voltage value is not in the range of -10% to +10%.
- Current alarms when output current value is over 100%.
- Temperature alarms when monitor panel temperature is lower than -20 or higher than 75 degrees Celsius.
- Relay alarm is normally closed contact. (For the two contacts, short circuit when power source is normal; open circuit when power source is abnormal.)

CE Standards

EN 55032, EN 55024,
EN 61000-3-2, EN 61000-3-3,
(EN 61000-4-2, EN 61000-4-3,
EN 61000-4-4, EN 61000-4-5,
EN 61000-4-6, EN 61000-4-8,
EN 61000-4-11)
Heavy Industry level, criteria A
LVD: EN 62368-1:2014

Safety Standards



UL 508 Meet



CE Marking

Environments

Operating Temperature -15 ~ 60°C, Ambient

Operating Humidity 20 ~ 90% RH, No Condensing

Storage Temperature -20 ~ 85°C, Ambient

Vibration 2G, 10~500Hz, 3 axes

NOTE

1. Each output can provide up to maximum load, but total load can not exceed rated output power.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
4. Ripple & Noise are measured with 20MHz oscilloscope at 220VAC by using a 20cm long 12" twisted pair-wire with a 0.1uF/630V metal capacitor & a 47uF electrolytic capacitor parallel on the test point.
5. Efficiency is measured at rated load and 220VAC input.
6. Hold-up time is measured at rated load and 220VAC input.
7. Output Voltage Adjustable is measured on 5% of rated load.
8. Reign Power reserve the right to change specifications at any time without notice.

WEB : <http://www.switching-powers.com>
E-mail : rp21003f@ms7.hinet.net

Tel : 886-2-22997550
Fax : 886-2-22997596

