



All the patents are held accountable counterfeiting.

Features



Green Power

- Adjustable output voltage and LED display on the panel
- Standard/Din Rail Mounting Dual Purpose, meet EU EN 43880 installation dimension standard 2SU
- No-load Consumption is lower than 0.3W
- Comply with High Efficiency Power 80Plus Criterion
- Comply with 2010. Energy Conservation Power Erp Regulation
- Convection cooled high reliability
- 2 years warranty
- Output modify range: 3V~200VDC

DIMENSIONS:52.5(H)*90.7(D)*35(W)mm

WEIGHTS: 117g

General specifications

INPUT

Input range

90~264VAC
127~380VDC

Input frequency

47~63Hz

Max. I/P current / Inrush current (25°C)

0.52A/40A@110VAC
0.33A/80A@220VAC

No Frame Ground Design

OUTPUT

Hold-up time

13ms

Short protection

Autorecovery

Over load protection

Automatic power limited

Detail specifications

20~25 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) ¹			Ripple & Noise ⁴	Line REG. ²	Load REG. ³	Efficiency ⁵	O.V.P
		Min.	Rated	Max.					
DLP1020D-05S	V : +5V ±10%	0A	4A	4A	80mV	±1%	±1%	82% Ref.	7.13 ~ 7.88V
DLP1025D-12S	V : +12V ±10%	0A	2.1A	2.1A	120mV	±1%	±1%	85% Ref.	17.1 ~ 18.9V
DLP1025D-24S	V : +24V ±10%	0A	1A	1A	240mV	±1%	±1%	86% Ref.	31.4 ~ 34.7V
DLP1025D-48S	V : +48V ±10%	0A	0.52A	0.52A	480mV	±1%	±1%	86% Ref.	64.6 ~ 71.4V

CE Standards

EN 55032, EN 55035,
EN 61000-3-2, EN 61000-3-3,
(EN 61000-4-2, EN 61000-4-3,
EN 61000-4-4, EN 61000-4-5,
EN 61000-4-6, EN 61000-4-8,
EN 61000-4-11)
LVD: EN 62368-1

Safety Standards



UL 508 Meet



CE Marking



Double Insulated

Environments

Operating Temperature

-15 ~ 50°C, Ambient

Operating Humidity

20 ~ 90% RH, No Condensing

Storage Temperature

-20 ~ 85°C, Ambient

Vibration

2G, 10~500Hz, 3 axes


NOTE

1. Each output can provide up to maximum load, but total load can not exceed rated output power.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
4. Ripple & Noise are measured with 20MHz oscilloscope at 220VAC by using a 20cm long 12" twisted pair-wire with a 0.1uF/630V metal capacitor & a 47uF electrolytic capacitor parallel on the test point.
5. Efficiency is measured at rated load and 220VAC input.
6. Hold-up time is measured at rated load and 220VAC input.
7. Output Voltage Adjustable is measured on 5% of rated load.
8. Reign Power reserve the right to change specifications at any time without notice.



All the patents are held accountable counterfeiting.

Mechanical Details



Panel Designation

CASE NO. : CS025D
UNIT : mm
DIMENSION : 52.5(H)*90.7(D)*35(W)
MATERIAL : PLASTIC
COLOR : BLACK

Symbol	Description
N	Neutral Terminal Of AC Input (No Polarity At DC Input)
L	Line Terminal Of AC Input (No Polarity At DC Input)
V-	DC Negative Output Terminal
V+	DC Positive Output Terminal
LED	Green LED Indicator
V adj.	Potentiometer For Output Voltage