



All the patents are held accountable counterfeiting.

Features

- Din Rail/ Screw Mounting Dual Purpose
- No-load Consumption is lower than 0.3W
- Comply with High Efficiency Power 80Plus Criterion
- Comply with 2010. Energy Conservation Power ErP Regulation
- Output Voltage Digital Display
- 100% burn-in test
- Convection cooled
- 1 year Warranty
- Output modify range: 3V~200VDC

Green Power



DIMENSIONS : 100(H) x 83(D) x 49(W)mm
WEIGHTS: 380g



General specifications

INPUT

Input range	90~132/180~264VAC (Selectable) 220~380VDC
Input frequency	47~63Hz
Inrush current (25°C)	20A/ 110VAC 40A/ 220VAC

OUTPUT

Hold-up time	13mS
Short protection	Autorecovery

Detail specifications



150 Watts

MODEL	O/P Volt Adj. \pm %	Load(Current) ¹			Ripple & Noise ⁴	Line REG. ²	Load REG. ³	Efficiency ⁵	O.V.P
		Min.	Rated	Max.					
LP1150D-12MA	V1: +12V \pm 10%	0A	12.5A	12.5A	150mVp-p	\pm 1%	\pm 2%	85% Ref.	28 ~ 34V
LP1150D-24MA	V1: +24V \pm 10%	0A	6.25A	6.25A	300mVp-p	\pm 1%	\pm 2%	86% Ref.	28 ~ 34V

EMC Standards

EN55022 CLASS A
EN61000-3-3
EN55024(IEC61000-4-2,
IEC61000-4-3, IEC61000-4-4
IEC61000-4-5, IEC61000-4-6
IEC61000-4-8, IEC61000-4-11)

Safety Standards

 UL/CSA 60950 Meet
 CE Marking

Environments

Operating Temperature -15 ~ 50C, Ambient
Operating Humidity 5 ~ 95% RH, No Condensing
Storage Temperature -20 ~ 85C, Ambient
Vibration 2G, 10~500Hz, 3 axes

- NOTE:**
1. Each output can provide up to maximum load, but total load can not exceed rated output power.
 2. Line regulation is measured from low line to high line at rated load.
 3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
 4. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.
 5. Efficiency is measured at rated load and 220VAC input.
 6. Hold-up time is measured at rated load and 220VAC input.
 7. Reign Power reserve the right to change specifications at any time without notice.