



Features



DIMENSIONS : 151(L) x 99(W) x 50(H)mm

- Fan cooled
- 100% burn-in test
- Build-in line filter
- Great reliability
- MOSFET designed
- 240,000 Hrs MTBF per MIL-HDBK-217F
- 1 year Warranty
- **Output modify range: 3V~200VDC**
- **Split rail & Series connection possible**

General specifications

INPUT

Input range	90~132/180~264VAC (Selectable) 220~380VDC
Input frequency	47~63Hz
Inrush current (25°C)	25A/110VAC 50A/220VAC

OUTPUT

Hold-up time	13mS
Short protection	Autorecovery
Overload protection	Automatic power limited

Detail specifications

250 ~ 350 Watts

MODEL	O/P Volt Adj. \pm %	Load(Current) ¹			Ripple & Noise ⁴	Line REG. ²	Load REG. ³	Efficiency ⁵	O.V.P Trip Point
		Min.	Rated	Max.					
LP1250-05M	V1: +5V \pm 10%	0A	50A	50A	80mVp-p	\pm 1%	\pm 1%	74% Min.	6.67 ~ 7.88V
LP1300-12M	V1: +12V \pm 10%	0A	25A	25A	120mVp-p	\pm 1%	\pm 1%	75% Min.	17.1 ~ 18.9V
LP1300-24M	V1: +24V \pm 10%	0A	12.5A	12.5A	240mVp-p	\pm 1%	\pm 1%	77% Min.	31.4 ~ 38.3V
LP1300-48M	V1: +48V \pm 10%	0A	6.25A	6.25A	480mVp-p	\pm 1%	\pm 1%	79% Min.	64.4 ~ 74.1V
LP1350-36M	V1: +36V \pm 10%	0A	9.7A	9.7A	200mVp-p	\pm 1%	\pm 1%	85% Min.	48.5 ~ 53.6V

EMC Standards

EN55022 CLASS A
EN61000-3-3
EN55024(IEC61000-4-2,
IEC61000-4-3, IEC61000-4-4
IEC61000-4-5, IEC61000-4-6
IEC61000-4-8, IEC61000-4-11)

Safety Standards

UL/CSA 60950 Meet
 CE 60950 Marking

Environments

Operating Temperature -15 ~ 50C, Ambient
Operating Humidity 5 ~ 95% RH, No Condensing
Storage Temperature -20 ~ 85C, Ambient
Vibration 2G, 10~500Hz, 3 axes

- NOTE:**
1. Each output can provide up to maximum load, but total load can not exceed rated output power.
 2. Line regulation is measured from low line to high line at rated load.
 3. Load regulation is measured from 20% to 100% of rated load at 110VAC input.
 4. Ripple & Noise is measured by using a 0.1uF/630V metalized capacitor & a 47uF electrolytic capacitor parallel on the test point, at rated load and 110VAC input.
 5. Efficiency is measured at rated load and 110VAC input.
 6. Hold-up time is measured at rated load and 110VAC input.
 7. Reign Power reserve the right to change specifications at any time without notice.