



All the patents are held accountable counterfeiting.

Features



- **Din Rail/ Screw Mounting Dual Purpose**
- **Fan speed control(PCB damp proof process)**
- **Wide input range**
- **100% burn-in test**
- **MOSFET designed**
- **1 years Warranty**
- **Output modify range: 3V~200VDC**

DIMENSIONS:100(H)*110(D)*60(W)mm
WEIGHTS: 600g

General specifications

INPUT

Input range	90~132/180~264VAC (Selectable) 220~380VDC
Input frequency	47~63Hz
Inrush current (25° C)	20A/ 110VAC 40A/ 220VAC

OUTPUT

Hold-up time	10mS
Short protection	Autorecovery

Detail specifications



350 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) ¹			Ripple & Noise ⁴	Line REG. ²	Load REG. ³	Efficiency ⁵	O.V. P
		Min.	Rated	Max.					
LP1350D-24M	V1: +24V ±10%	0A	14.6A	14.6A	240mVp-p	±1%	±2%	79% Min.	31.4 ~ 38.3V

EMC Standards

EN55022 CLASS A
EN61000-3-3
EN55024(IEC61000-4-2,
IEC61000-4-3, IEC61000-4-4
IEC61000-4-5, IEC61000-4-6
IEC61000-4-8, IEC61000-4-11)

Safety Standards

 UL/CSA 60950 Meet
 CE Marking

Environments

Operating Temperature -15 ~ 50°C, Ambient
Operating Humidity 5 ~ 95% RH, No Condensing
Storage Temperature -20 ~ 85°C, Ambient
Vibration 2G, 10~500Hz, 3 axes

- NOTE:**
1. Each output can provide up to maximum load, but total load can not exceed rated output power.
 2. Line regulation is measured from low line to high line at rated load.
 3. Load regulation is measured from 20% to 100% of rated load at 110VAC input.
 4. Ripple & Noise is measured by using a 0.1uF/630V metalized capacitor & a 47uF electrolytic capacitor parallel on the test point, at rated load and 110VAC input.
 5. Efficiency is measured at rated load and 110VAC input.
 6. Hold-up time is measured at rated load and 110VAC input.
 7. Reign Power reserve the right to change specifications at any time without notice.